

OUTPUT RATINGS 50 Hz / 400 V 60 Hz / 480 V		
Stand By Power	135	
	108	
Prime Power	150	
	120	

ENGINE TECHNICAL DATA		
Engine Model	Perkins 1106-70TG1	
Number of Cylinders	6 / Inline	
Cycle	4 Stroke	
Bore / Stroke [mm] :	105 / 130	
Induction :	Turbocharged	
Cooling Method :	Water	
Governor Type :	Mechanical	
Compression Ratio :	18,2:1	
Displacement [lt] :	7,01	
Electrical Sys. Voltage	12 / Negative	
Battery Charger Amps	55	

ALTERNATOR DATA		
Manufacturer	Maranello	
Model	M150	
No. of Bearings :	Single	
Insulation Class:	H	
Winding Pitch :	2/3	
Number of Wire :	12	
Protection Class :	IP23	
Efficiency:	92,6%	
Voltage Regulation (Steady State) :	1,0%	
Total Harmonic Content:	4,0%	
Apparent Power (kVA)	169	
Radiant Heat [Kw]:	50 Hz	
	60 Hz	

Dimension (WxHxL)	
CONOPIED	1100x1950x3440
OPEN SET	1100x1480x2650

WEIGHT (KG)	
CONOPIED	1670
OPEN SET	1297

FUEL TANK (LT)	
CONOPIED	400
OPEN SET	400

AVAILABLE OPTIONS

AYPOWER offers a range of optional features to tailor our gensets to meet your power requirements.

Options:

- * A wide range of Sound Attenuated Enclosures
- * A variety of generating set control and synchronising panels
- * Additional alarms and shutdowns
- * A selection of exhaust silencer noise levels

For further information on all of the standard and optional features for this product, please contact AYPOWER or visit www.aypowergenerator.com

Prime Rating: These ratings are applicable for supplying continuous electrical power (at variable load) of commercially purchased power. There is no limitation to the annual hours of operation, this model can supply 10% overload power 1 hour in each 12 hours.

Standby Rating: These ratings are applicable for supplying continuous electrical power (at variable load) in the event of an utility power failure. No overload is permitted on these ratings. The alternator on this model is peak continuous rated (as defined in ISO 8528)

Standard Reference Conditions: Standart reference conditions 25°C Air Inlet Temp. 100m, 30% relative humidity.

